

TITAN[®]

HELIX FR28



INNOVATIVE PERFORMANCE MADE SIMPLE

INTRODUCING THE FUTURE OF ELECTRIC FOAM PROPORTIONERS

The Helix FR28 provides unmatched accuracy and heating efficiency. The key features provide balanced pressure, less wasted material and direct heat from the system all the way to the gun. With a user-friendly design – allowing for simple operation and inexpensive maintenance – the FR28 offers better results and increased ROI.

Smart Connect Dual Pump System

- ▶ Delivers equal amounts of the A and B component increasing yield and chemical performance
- ▶ Improves accuracy by 3-5%
- ▶ Independent priming and flushing

First Electronically Controlled Dual System Proportioner

- ▶ Continual communication between pumps
- ▶ Synchronizes ratio 64 times per motor revolution

33% Lighter Than Most Comparable Equipment

Available in Single Phase, 48 Amp
Customizable to 3 phase if needed.



MULTIPLE APPLICATIONS

The Helix FR28 is designed to spray two component open and closed cell foam insulation for:

- ▶ **RESIDENTIAL**
- ▶ **COMMERCIAL**
- ▶ **INDUSTRIAL**

TITAN HAS JUST TAKEN DUAL COMPONENT APPLICATORS TO THE NEXT LEVEL.

Delivering performance, durability and innovation never before seen in a foam insulation sprayer.

Features and Benefits

Integrated Electronic Proportioning

Proprietary system synchronizes both pumps to maintain an ultra-accurate ratio.

SureFire™ Hose Heater

Heats the coating all the way from the block heater to the end of the hose. Additionally, the temperature can be adjusted at the gun where it matters most.

SureFire™ Block Heater

Maximizes surface area and dwell time for heater efficiency and maximizes the time in the heater. More time and surface area means more efficient heating.

Universal Siphon/Draw

Modular design allows for transfer pump or direct feed.

Universal Power Adapter

Plug into shore power, generator or hardwire into a system.

Lightweight and Compact Design



33% lighter than most comparable equipment.

Quad+™ Packings

Self-adjusting packings deliver high performance and long life.

EasyOut™ Fluid Section

Change fluid section on-site in minutes and reduces downtime to keep you spraying.





Helix FR28

SPECIFICATIONS

Max. Pressure	2000 PSI (136 MPa)
Max. Material Temp.	140°F (60°C)
Output	28 lbs/min (12.7 kg/min)
Hose Length	Standard with 200' (60 m)
Footprint	30" x 27" x 37" (76.2 cm x 69 cm x 93 cm)
Weight	273 lbs (123 kg)
Electrical Supply	230 V 1 Phase 48 Amps with standard 6,000 Watt Heater

SUREFIRE™ HEATING SYSTEM

A super efficient heating system designed to save you time and money

The Helix FR28's advanced heating system provides direct heat starting the instant material enters the block heater and continuing all the way to the gun.



**SureFire™
Block Heater**

**Patented High
Efficiency Aluminum
Mass Heater**

**Wrap around design provides
over 30 seconds of dwell time**

- Greater surface area to heat chemical
- Longer dwell time versus competitive one pass design
- Internal turbulence increases heat transfer

Heating rod completely isolated from the coating

- No failure from chemical
- No failure from exposure to air when run dry
- Change power or repair without opening the system
- Modular – can stack two to four blocks (3 blocks standard)
- Easily customizable for 3 kW to 18 kW
- Heat with less power
- Requires a smaller generator



SureFire™ Hose Heater

- Actively controls temperature at the gun
- Heating element in the hose provides direct heat:
Adds heat all the way to the end of the hose
- True chemical temperature measured at the gun

ADDITIONAL ACCESSORIES



Transfer Pumps

- ▶ 1:1 and 2:1
- ▶ 55 gallon
- ▶ Bung mount
- ▶ Built to fit a 6' 7" trailer

1:1 Stainless Steel 0138762

2:1 Stainless Steel 0138760

PMC AP2 Spray Gun 0138799

- ▶ Proven reliability
- ▶ Spray, blast and pour nozzles available
- ▶ 10-40 lb. operation
- ▶ Lightweight and compact
- ▶ Modular design for ease of maintenance



THE INDUSTRY'S STRONGEST WARRANTY

Our Helix FR28 is the industry's most advanced Spray Foam Proportioner, so it is only fitting that the warranty be just as impressive. We stand behind our product a year longer than anybody else in the industry. To top it off, we guarantee our Titan motors for up to 4 years. So, if you are not only seeking a machine that will get the job done efficiently but also a team of support, Titan Helix is the choice for you.

**TWO-YEAR
DEFECTS
WARRANTY**

We warrant that our system is free from defects in materials and workmanship for two years. Does not apply in the case of damage caused by abrasion, corrosion, misuse, negligence, accident, faulty installation, substitution of non-Titan component parts or tampering with the unit in a manner to impair normal operation. Excludes normal wear items and consumables such as, filters, pistons, packing's, tips, etc.

**FOUR-YEAR
MOTOR
WARRANTY**

We warrant that our motor is free from defects in materials and workmanship for four years. If the motor fails for any reason (including wear) in the first 4 years of ownership; we will replace the motor at no cost to you.



CONNECTOR APP

Available for download
theconnectorapp.com

Call Technical Services at
1-844-458-1215
for complete warranty information.

All information contained in this brochure is based on the latest information available at the time of printing. Titan reserves the right to make changes at any time, without notice. Due to continuous innovation, specifications may progressively change. Contact one of our dependable sales reps or call our dedicated customer service team for more information.