

**WAGNER**

**SuperFinish  
Crack Repair**



## SuperFinish Crack Repair

- Precise, user-friendly and efficient in crack filling and redevelopment
- QLS - Quality Long Stroke diaphragm pump ideal for both high and low viscosity materials
- Suitable for a range of materials: epoxy, polyurethane (PU), SPUR foam and aqueous solutions
- Suitable for use in concrete repair works

# SF23 Pro Crack Repair

- QLS - Quality Long Stroke diaphragm pump ideal for both high and low viscosity materials
- Suitable for a range of materials: epoxy, polyurethane (PU), SPUR foam and aqueous solutions
- Versatile and robust - perfect all rounder for multiple applications for demanding construction site usage
- Lightweight, compact and easy to maneuver
- Available with 5L or 20L Hopper



## INCLUSIONS

SF23 Pro Crack Repair 5L	2395486CR5	SF23 Pro Crack Repair 20L	2395486CR20
15m airless hose	2390608	15m airless hose	2390608
5 litre hopper	0341265	20 litre hopper	0341266
HEA pressure gauge	0340257	HEA pressure gauge	0340257
Injection Lance with ball valve	700-100C	Injection Lance with ball valve	700-100C
Tool bag; incl. wrenches 41mm/22mm/19mm and screw driver	2391822	Tool bag; incl. wrenches 41mm/22mm/19mm and screw driver	2391822

# SF33 Pro Crack Repair

- Precise, user-friendly and efficient in crack filling and redevelopment
- QLS - Quality Long Stroke diaphragm pump ideal for both high and low viscosity materials
- Suitable for a range of materials: epoxy, polyurethane (PU), SPUR foam and aqueous solutions
- Versatile and robust - perfect all rounder for multiple applications and for demanding construction site usage
- Large shock absorbing wheels
- Single position cart with hopper and built in tool box
- Ideal for large volume applications



## INCLUSIONS

SF33 Pro Crack Repair 5L	2409323CR5	SF33 Pro Crack Repair 20L	2409323CR20
15m airless hose DN6	9984574	15m airless hose DN6	9984574
5 litre hopper	0341265	20 litre hopper	0341266
Pressure gauge	2383994	Pressure gauge	2383994
Injection Lance with ball valve	700-100C	Injection Lance with ball valve	700-100C
Tool bag; incl. wrenches 41mm/22mm/19mm and screw driver	2391822	Tool bag; incl. wrenches 41mm/22mm/19mm and screw driver	2391822

# SF23 HD Crack Repair **NEW**

Specifically designed for use as a pump for crack repair, masonry restoration; for combatting moisture and water damage, and for concrete restoration.

The stainless steel pump head and the diaphragm have been specially adapted to the special loads for use in crack repair and grouting.

- Stainless steel pump head for long life and toughness against harsh materials
- Stainless steel valve with pressure regulator for control of smooth flow of material
- Telescopic handle for ease of movability
- Stainless steel fitting on pump head and valves to facilitate the use on all different types of crack repair applications
- Large shock absorbing wheels for ease of moving over those uneven worksites
- Robust Frame for the tough environments
- Push and ball valve for a direct prime and application procedure



## INCLUSIONS

<b>SF23 HD Crack Repair 5L</b>	2415601HD5
SF23 HD Spray Bare	2415601
5L Hopper	0341265
HEA Pressure Gauge	0340257
Injection Lance with ball valve	700-100C
15 Mtr Hose 3625 PSI	2390608

<b>SF23 HD Crack Repair 20L</b>	2415601HD20
SF23 HD Spray Bare	2415601
20L Hopper	0341266
HEA Pressure Gauge	0340257
Injection Lance with ball valve	700-100C
15 Mtr Hose 3625 PSI	2390608

## OPTIONAL ACCESSORIES

- Rigid Suction Kit available - sold separately
- Flexible Suction Kit available - sold separately



# WAGNER

## FOR PRECISE CRACK REPAIR

### Ball Valve

Stainless Steel  
Easy prime to spray  
positioning

### Push Valve

For reliable operation

### Robust Cart

Horizontal positioning with  
telescopic handle. Designed for  
tough environments and easy  
to transport

### 5L or 20L Hopper


Can be used with hopper  
and return hose

### Stainless Steel Paint Head

For long life  
& toughness against  
harsh materials

## THE BENEFITS OF DIAPHRAGM PUMP TECHNOLOGY

Diaphragm pumps are a great choice when it comes to handling a wide variety of materials, from thin liquids to high-viscosity paints. QLS technology and low stroke frequency puts less stress on the components, significantly extending the service life of the pump and reducing maintenance costs. Valves are made of wear-resistant carbide and the diaphragm is made of solvent resistant polyamide.



## TECHNICAL DATA

	SF23 Pro Crack Repair	SF23 HD Crack Repair	SF33 Pro Crack Repair
Part Number:	2395486CR5	2415601HD5	2409323CR5
Motor Rating:	1.3 kW	1.3 kW	2.2 kW
Lance Included:	Injection Lance Complete	Injection Lance Complete	Injection Lance Complete
Hose Length:	15 m	15 m	15 m
Max. Operating Pressure:	3600 psi	3625 psi	3600 psi
Max. Flow Rate:	2.6 l/min	2.6 l/min	4.3 l/min
Weight:	27 kg	37 kg	43 kg

### SF23 PRO CRACK REPAIR



AVAILABLE  
WITH 5L OR  
20L HOPPER

### SF23 HD CRACK REPAIR



AVAILABLE  
WITH 5L OR  
20L HOPPER

### SF33 PRO CRACK REPAIR



AVAILABLE  
WITH 5L OR  
20L HOPPER

WAGNER SPRAYTECH AUSTRALIA PTY LTD  
8 Dansu Crt, Hallam VIC 3803  
FREECALL 1800 924 637  
info@wagneraustralia.com.au  
www.wagneraustralia.com.au

PAINTWORX (NZ)  
70 Lady Ruby Drive, East Tamaki, Auckland  
Ph: 09 272 2840 Fax: 0800FOR WAGNER  
service@paintworx.co.nz  
www.wagner.co.nz



WAG0922-01